

COYLE ANIMAL MARKER BLACK NPD8833

Page: 1

Compilation date: 14/06/2021

Revision date: 20/09/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: COYLE ANIMAL MARKER BLACK NPD8833

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Coyle Veterinary Distributors Ltd

Kilkerrin Park

Liosban Industrial Estate

Galway

County Galway

Ireland

Tel: 091 753375/0872569844 **Email:** coylevet@eircom.net

1.4. Emergency telephone number

Emergency tel: 091 753375/0872569844

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Skin Irrit. 2: H315; STOT SE 3: H336; Aquatic Chronic 2: H411; Flam. Aerosol 1: H222; -:

H229

Most important adverse effects: Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin

irritation. May cause drowsiness or dizziness. Toxic to aquatic life with long lasting

effects.

2.2. Label elements

Label elements:

Hazard statements: H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark GHS09: Environmental







COYLE ANIMAL MARKER BLACK NPD8833

Page: 2

Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P362+P364: Take off contaminated clothing and wash it before reuse.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122

°F.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-151-9	64742-49-0	-	Aquatic Chronic 2: H411; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3:	30-50%
			H336	

PETROLEUM GASES, LIQUEFIED

270-704-2	68476-85-7	Substance with a Community	Flam. Gas 1: H220; Press. Gas: H280	30-50%
		workplace exposure limit.		

MINERAL OIL

-	-	Substance with a Community	-	1-10%
		workplace exposure limit.		

D40 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, DE-AROMATISED - REACH registered number(s): 01-2119463258-33-XXXX

919-857-5	64742-48-9	-	Flam. Liq. 3: H226; STOT SE 3: H336;	1-10%
			Asp. Tox. 1: H304; -: EUH066	

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Do not induce vomiting. Consult a doctor.

COYLE ANIMAL MARKER BLACK NPD8833

Page: 3

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Extremely flammable. In combustion emits toxic fumes. Forms explosive air-vapour

mixture. Vapour may travel considerable distance to source of ignition and flash back.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Eliminate all sources of

ignition. If outside do not approach from downwind.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Do not use equipment in clean-up procedure which may

produce sparks. Clean-up should be dealt with only by qualified personnel familiar with

the specific substance.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

Smoking is forbidden. Use non-sparking tools.

COYLE ANIMAL MARKER BLACK NPD8833

Page: 4

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from direct

sunlight. Keep away from sources of ignition.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PETROLEUM GASES, LIQUEFIED

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
IE	1800 mg/m3	2250 mg/m3	-	-

MINERAL OIL

EU	1 5mg/m3	10mg/m3	-	-
----	----------	---------	---	---

DNEL/PNEC Values

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	773mg/kg/day	Workers	Systemic
DNEL	Inhalation	2035mg/m3	Workers	Systemic
DNEL	Dermal	699mg/kg/day	Consumers	Systemic
DNEL	Inhalation	608mg/m3	Consumers	Systemic
DNEL	Oral	699mg/kg/day	Consumers	Systemic

D40 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, DE-AROMATISED

Type	Exposure	Value	Population	Effect
DNEL	Dermal	208mg/kg/day	Workers	Systemic
DNEL	Inhalation	871 mg/m3	Workers	Systemic
DNEL	Dermal	125mg/kg/day	Consumers	Systemic
DNEL	Inhalation	185mg/m3	Consumers	Systemic
DNEL	Oral	125mg/kg/day	Consumers	Systemic

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

COYLE ANIMAL MARKER BLACK NPD8833

Page: 5

Respiratory protection: Respiratory protection not required.

Hand protection: Chemically resistant gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Aerosol

Colour: Black

Odour: Characteristic odour

Flash point°C: <23

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Direct sunlight. Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

COYLE ANIMAL MARKER BLACK NPD8833

Page: 6

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

DERMAL	RAT	LD50	>2000	mg/kg
GASES	RAT	4H LC50	>20	mg/l
ORAL	RAT	LD50	>2000	mg/kg

D40 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, DE-AROMATISED

DERMAL	RBT	LD50	>5000	mg/kg
GASES	RAT	4H LC50	>5000	mg/l
ORAL	RAT	LD50	>5000	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

NAPHTHA (PETROLEUM) HYDROTREATED, LIGHT, LOW BOILING POINT

ALGAE	72H IC50	<10	mg/l
DAPHNIA	48H EC50	<10	mg/l
FISH	96H LC50	<10	mg/l

D40 NAPHTHA (PETROLEUM), HYDROTREATED HEAVY, DE-AROMATISED

ALGAE	72H IC50	>1000	mg/l
Daphnia magna	48H EC50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

COYLE ANIMAL MARKER BLACK NPD8833

Page: 7

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Recovery operations: Not applicable. **Disposal of packaging:** Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

Shipping name: AEROSOLS

14.3. Transport hazard class(es)

Transport class: 2

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: Yes Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

COYLE ANIMAL MARKER BLACK NPD8833

Page: 8

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H220: Extremely flammable gas.

H222: Extremely flammable aerosol.

H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H229: Pressurised container: May burst if heated.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information in

this MSDS is only considered accurate at the time of its creation. During this time

classifications of substances may change. Therefore it is possible that can art work and

MSDS information may differ. As such if you have any concerns we recommend you

request a new MSDS from us every 6-12 months.