


MILKSTONE REMOVER

PHOSPHORIC ACID BASED DESCALER DESIGNED FOR THE REMOVAL OF SCALE DEPOSITS IN MILKING EQUIPMENT AND BULK MILK TANKS

- Effective in the removal and prevention of milkstone and water deposits
- Can be used in hot or cold solutions
- Can be used in both pipeline machines and bucket plants
- Removes iron and rust stain



RECOMMENDED USAGE



INSTRUCTIONS

ALWAYS ADD PRODUCT TO WATER AND NOT WATER TO PRODUCT.



For light deposits and spot treatment 1 litre of product should be added to 100 litres of water (1%).

For general milkstone removal and descaling 2 litres of product should be added to 100 litres of water (2%).



Hot water gives best and quickest results although warm or cold water can be used. The solution should have 10 minutes contact time with the equipment. After having rinsed this solution, a detergent solution should be circulated through the plant.



Storage: Store in a dry area away from alkaline and chlorinated products

Pack Size: 4x5, 25 & 200 litre

Shelf Life: 2 years from date of manufacture

FOR HEALTH & SAFETY INFORMATION, REFER TO THE SAFETY DATA SHEET

KILCO (INTERNATIONAL) LTD.
BROOMHOUSES 2 INDUSTRIAL ESTATE
OLD GLASGOW ROAD, LOCKERBIE.
DG11 2SD

Tel: +44 (0) 1576 205 480
Fax: +44 (0) 1576 205 483
Email: enquiries@kilco.co.uk

