

ALL PURPOSE FILLER EASI SQUEEZE

| Colour | Product Code | Pack Size | Box Qty |
|--------|--------------|-----------|---------|
| White | READYINST | 330G | 12 |

Product Description

EVERBUILD ALL PURPOSE READY MIXED FILLER EASI SQUEEZE is an easy to use ready mixed filler with quick drying properties, which makes the product ideal for instant repairs to minor surface imperfections in most porous surfaces e.g. plaster, wood, render etc. When applied as directed, the filler dries to a smooth but tough crack resistant sandable finish that may be painted, papered or stained. This filler is suitable for both internal and external use.

Benefits

- Extremely quick drying formula.
- Interior or exterior use.
- Overpaintable with most solvent based and emulsion paints.
- Overstainable
- Dries white.

Areas For Use

Fills gaps and holes in:

- Plaster
- Brick
- Stone
- Wood
- Render

Limitations

- Do not use to fill plastic or metals.
- For fine surface holes only. Do not apply more than 5mm deep.
- Not suitable for repairs to permanently wet areas.
- Do not apply or allow to dry below 5°C.
- Drying time will be approximately 10mins at 20°C for very minor imperfections. This will increase substantially with increased depth, lower temperatures or when used externally.
- As the manufacturer cannot know all the uses its products may be put to, it is the users responsibility to determine suitability for use. If in doubt, contact technical services department for advice or refer to technical data sheet.
- Do not apply externally when rain is imminent (within 5 hours of application).

Surface Preparation

All surfaces must be clean, dry, free from dust, grease and other contamination. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

Application

Before applying, ensure surfaces are clean, dry, sound and free from dust or any contaminants, which may affect adhesion. Provide a key to gloss painted surfaces. Cover nail or screw heads with oil based paint and allow to dry.

Remove cap and cut nozzle to required aperture. Squeeze directly into hole or crack and level with a filling knife. Note; do not exceed 5mm depth in one application For greater depth, build up in individual layers. Once dry, sand to a smooth finish. When used outdoors, seal the repair with oil based paint once dry.

Specific Data

| | |
|-------------------------|--|
| Appearance | White / Off White Paste |
| S.G. at 20°C | 1.8 g/cm ³ (approx) |
| Movement Accommodation | Low – Dries hard |
| Maximum Fill | 5mm in one coat – further layers may be built up |
| Maximum Width | 25mm |
| Application Temperature | 5°C to 30°C. |
| Drying Time | 1 - 8 hours depending on depth and temperature |
| pH | 8.5-9.9 |
| Solids Content | 85 % w/w (APPROX) |

Health & Safety

Consult MSDS for full list of hazards.

Storage

Store at moderate temperatures. PROTECT FROM FROST

Shelf Life

24 months from date of manufacture when stored according to manufacturers instructions.

The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings that result from technological changes or research between the date of issue of this document and the date the product is acquired. Before using the product, the user should carry out any necessary tests in order to ensure that the product is suitable for the intended application. Moreover, all users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, whether for normal use or a specific application of our product. Our guarantee applies within the context of the statutory regulations and provisions in force, current professional standards and in accordance with the stipulations set out in our general sales conditions. The information detailed in the present technical data sheet is given by way of indication and is not exhaustive. The same applies to any information provided verbally by telephone to any prospective or existing customer.