

TECHNICAL DATA SHEET

Date: 12 July 2018
Version: 1002
Pages: 1

Arc Cable Ties

DESCRIPTION:

Manufactured from high grade Nylon 6.6 giving strength and flexibility.

Manufactured in lengths from 100mm up to 880mm they are suitable for many applications, servicing the electronics, heavy electrical, engineering & DIY industries.

Flame Resistance:

In accordance with UL94V2

Temperature Range:

For continuous use -40°C to +85°C

Technical Data:

LENGTH (mm)	WIDTH (mm)	MIN LOOP
		TENSILE STRENGTH (kg)
100	2.5	8
140	3.6	18
200	4.8	22
300	4.8	22
360	4.8	22
430	4.8	22
500	4.8	22
365	7.6	55
450	7.6	55
540	7.6	55
610	9	80
750	9	80
880	12.4	110

All products should be sold in accordance with the manufacturer's instructions. The manufacturer cannot be held responsible where conditions of use are beyond our control. Arc Building Products products are available for sale in accordance with Arc Building Products standard conditions of sale, which is available upon request. Whilst any information contained herein is to the best of our knowledge true and accurate, no warranty is given or implied in connection with any recommendations or suggestions made by us, our representatives, agents, or distributors, as the conditions of use, and any labour involved is beyond our control. Our warranty is therefore limited to the quality of supplied product.